
## Auralux100.

High-Performance StudioLED FRESNEL Manual Zoom

High performance LED fresnels with a variable beam of pure white light.





Specially created for cinematographers, television, video and photography producers and filmmakers alike, this powerful Fresnel, features a variable beam, with pure white light blended with our unique NEBULA® Diffusion Chamber.

The luminaire emits a light beam that produces defined shadows and beautiful skin and stage color rendition with a CRI and TLCI > 93.










Specially created for cinematographers, DP's, television, video and photography producers and filmmakers alike, this powerful 103 W 5.5" Fresnel, features a variable beam, with pure white light blended with our unique NEBULA® Diffusion Chamber Technology.


Model	AuraLux 100® Tungsten	AuraLux 100® Daylight	
Code	G6LED171	G6LED172	
Code with Pole Operated	G6LED180	G6LED181	
Operation	100-240V - 50/60Hz	100-240V - 50/60Hz	
Weight lb/kg	13.29/6.03	13.29/6.03	
Electrical draw	.86 (103 W) @120VAC	.86 (103 W) @120VAC	
Color temperature	3200K	5600K	
CRI	>93	>90	
Remote dimming control	Via DMX 0% - 100%	Via DMX 0% - 100%	
Local dimming control	Digital Display 0% - 100%	Digital Display 0% - 100%	
		Manual from 10°-40°	

## **Technical specifications**

- Available in 2 versions: Tungsten 3200K or Daylight 5600K
- 50,000 hours long Life LED
- Powerful LED engine with very low 103 W electrical draw
- 100 240VAC 50/60Hz VAC
- Quiet operation
- Exclusive NEBULA® Diffusion Chamber a beautiful high CRI and TLCI variable beam light for defined shadows & color rendition



Photometric	Data	6.00 ft	9.00 ft	12.00 ft
Illuminance E Foot-Candles/lux		 	i	!
AuraLux 100® High Performance Tungsten		i	E 104 fc	E 58 fc
Auralyxioe	FLOOD: 45°	E 232 fc	E 1,144 fc	E 641 fc
	SPOT: 9°  FLOOD: 45°	E 27,600 lx	E 12,311 lx	E 6,900 lx
		E 2,500 lx	E 1,115 lx /	E 625 lx /
				,





## **Each fixture comes with:**



Barndoors - 8 Blades G6LED120



Filter Holder G6LED097



C-Clamp G6FLT262



16 ft AC cord with Powercon conector G6CNT154



2 Safety Cables: 1 for barndoor 1 for fixture G6FLT059



Stand Mount Spigot Mini G6FLT086

